

I-60 ADS TEILKREISMODELL (40° - 360°)

Düse	Druck bar	Radius m	Durchfluss m³/h l/min	N.-Rate mm/h
 7 Orange	2,8	15,2	1,48 24,6	13
	3,4	15,9	1,61 26,9	13
	4,1	16,5	1,75 29,1	13
 10 Hellgrün	2,8	16,2	1,93 32,2	15
	3,4	17,1	2,16 36,0	15
	4,1	17,7	2,32 38,6	15
 13 Hellblau	2,8	17,1	2,39 39,7	16
	3,4	17,7	2,75 45,8	18
	4,1	18,3	2,95 49,2	18
 15 Grau	2,8	17,7	2,84 47,3	18
	3,4	18,3	3,16 52,6	19
	4,1	18,9	3,43 57,2	19
 18 Rot*	2,8	18,0	3,54 59,1	22
	3,4	18,9	3,98 66,2	22
	4,1	19,8	4,23 70,4	22
 20 Dunkelbraun	2,8	18,9	3,98 66,2	22
	3,4	19,5	4,34 72,3	23
	4,1	20,1	4,63 77,2	23

I-60 36 S VOLLKREISMODELL (360°)

Düse	Druck bar	Radius m	Durchfluss m³/h l/min	N.-Rate mm/h
 7 Orange	2,8	15,5	1,48 24,6	6
	3,4	16,5	1,70 28,4	6
	4,1	17,1	1,82 30,3	6
 10 Hellgrün	2,8	16,2	1,93 32,2	7
	3,4	17,1	2,16 36,0	7
	4,1	17,7	2,32 38,6	7
 13 Hellblau	2,8	17,1	2,39 39,7	8
	3,4	17,7	2,82 46,9	9
	4,1	18,3	2,95 49,2	9
 15 Grau	2,8	17,7	2,84 47,3	9
	3,4	18,3	3,18 53,0	10
	4,1	18,9	3,43 57,2	10
 18 Rot*	2,8	18,0	3,54 59,1	11
	3,4	18,9	4,02 67,0	11
	4,1	19,8	4,29 71,5	11
 20 Dunkelbraun	2,8	18,9	3,98 66,2	11
	3,4	19,5	4,34 72,3	11
	4,1	20,4	4,72 78,7	11