

DÜSEN FÜR EAGLE 950				
Düse	Druck bar	Radius m	Durchfluss m³/h	N.-Rate mm/h
 18-c Weiß	4,1	21,3	4,43	19
	4,5	21,7	4,64	20
	5,0	22,1	4,9,3	20
	5,5	22,5	5,19	20
	6,0	22,8	5,44	21
	6,5	23,0	5,68	21
	6,9	23,2	5,86	22
 20-c Grau	4,1	21,9	5,22	22
	4,5	22,6	5,48	22
	5,0	22,7	5,81	23
	5,5	23,2	6,12	23
	6,0	23,6	6,40	23
	6,5	24,0	6,69	23
	6,9	24,4	6,93	23
 22-c Blau	4,1	22,6	6,02	24
	4,5	22,9	6,29	24
	5,0	23,5	6,66	24
	5,5	24,4	7,01	23
	6,0	24,8	7,34	24
	6,5	25,3	7,64	24
	6,9	25,6	7,86	24
 24-c Gelb	4,1	23,2	7,00	26
	4,5	23,8	7,32	26
	5,0	24,7	7,75	25
	5,5	25,6	8,16	25
	6,0	26,5	8,56	24
	6,5	27,1	8,93	24
	6,9	27,4	9,20	24
 26 Orange	4,1	23,8	8,18	29
	4,5	24,4	8,50	29
	5,0	25,1	8,95	28
	5,5	25,6	9,41	29
	6,0	26,0	9,73	29
	6,5	26,5	10,18	29
	6,9	26,8	10,61	29
 28 Grün	4,1	-	-	-
	4,5	25,2	9,44	30
	5,0	25,8	10,00	30
	5,5	26,2	10,72	31
	6,0	26,9	10,93	30
	6,5	27,4	11,37	30
	6,9	27,7	11,86	31
 30 Schwarz	4,1	-	-	-
	4,5	25,2	10,44	33
	5,0	25,8	10,92	33
	5,5	26,2	11,43	33
	6,0	27,1	11,85	32
	6,5	27,7	13,30	32
	6,9	28,0	12,67	32
 32 Braun	4,1	-	-	-
	4,5	25,3	11,17	35
	5,0	25,7	11,60	35
	5,5	25,9	12,05	36
	6,0	26,6	12,46	35
	6,5	27,3	13,00	35
	6,9	28,0	13,49	34